

DIGITAL THERMO HYGROMETER

JR900A Dual Channel with external temperature

Product Description:

This is a professional digital thermohygrometer with internal and external temperature probe for temperature measurement. It has a wide range of applications in Ovens, Furnaces, Ceramics, Pottery, Molten Metal and many other industrial uses.

Warranty :

12 months warranty

New Technology:

ABS plastics provide a balanced combination of mechanical toughness, wide temperature range, good dimensional stability, chemical resistance, electrical insulating properties, and ease of fabrication. ABS plastic is available in a wide range of grades including medium and high-impact, heat-resistant, plateable fire-retardant, and both low and high gloss varieties.



• Features:

Large screen large font so that everything is clearly visible even watch also remains visible side! 3.4 inches large screen, black and white points a bright LCD screen display Plastic casing ABS 100 %

Maximum (MAX), Minimum (MIN) Temperature Measurement

Switchable between °C, °F

Displays the two temperature internal and external

Displays relative humidity

Specification:

Temperature range:

Temperature: -50°C~70°C (-58~158°F)

Humidity : 10%~99%RH

Resolution:

Temperature: 0.1°C (0.1°F)

Humidity: 1%RH

Accuracy:

Temperature: ±1°C (1.8°F)

Humidity: ±5%RH (40%~80%)

Power supply: 1.5V (AAA size) x1

Size: L115xW107xTH20MM



Side ventilation holes up and down. The left side of JR 900A are designed with air convection holes, when you hang the hygrometer on the wall or flat on the table, will not cause air convection holes will not be covered leading to poor air convection, test results appear biased



Crystal Calibration
Sales and Service co.,ltd.

CRYSTAL CALIBRATION SALES AND SERVICE CO., LTD

45/48 Soi Salathammasop31, Salathammasop Rd.,

Salathammaop, Thawewatthana, BKK Thailand 10170

Tel +668 9811 9446 Fax +662 889 6866

Email info@crystalcal.com Web site : www.crystalcal.com